



LIFTING CAPACITY	20 T										
	2450		2615		2635		2850		2900		
HOOKLIFT WEIGHT	4767	4967	5267	5467	5667	5867	6075	6275	6475	6675	6875
TOTAL LENGTH (E)	4500	4700	5000	5200	5400	5600	5800	6000	6200	6400	6600
HOOK-ROLLER CENTRE DISTANCE (C)	3900		4400		4600		5100		5300		
CONTAINER WORKING LENGTH (LC min)	5100	5300	5600	5800	6000	6200	6400	6600	6800	7000	7200
CONTAINER WORKING LENGTH(LC max)	1480										
HOOK HEIGHT (A)	-100	-60	0		40		65				
CONTAINER PICKING UP HEIGHT (H)	825	1025	825	1025	1025	1225	925	1125	1325	1325	1525
HOOKARM STROKE (N)	1060										
WIDTH OF THE FRAME	51°					52°					
MAX TILTING ANGLE (α)	44°/30°		41°/29°		42°/29°		37°/27°		38°/26°		
LOADING ANGLE (max/min)*	340					350					
OPERATING PRESSURE (bar)	60										
PUMP DELIVERY / 1000 r (Lt / min)	150										
OIL TANK (Lt)	2570	2600	2850	2880	2900	2940	3220	3280	3320	3380	3420
CENTRE OF GRAVITY (Dimension referred to sliding roller centre)											

* truck height 900 mm.